MONTVILLE TOWNSHIP TRUSTEES 6665 Wadsworth Rd, Medina, OH 44256

| APPLICATION FOR DRIVEWAY PE | RMIT Driveway Permit No. | Zoning Cert. No |
|--|-----------------------------------|------------------|
| Application is hereby made for drivewa | ay at | S/L |
| Name of Applicant: | | |
| Address of Applicant: | | |
| Telephone No | Cell Phone No | |
| Email: | Township Road N | lo |
| Proposed driveway to be along the N | E S W side of road | miles N E S |
| W of | (Nearest Intersecting Road, Stree | t, Drive etc.) |
| Type of proposed driveway: Resident | al Field Commercial C | Other |
| Proposed surface: Concrete Asp | halt Limestone Gravel C | Other |
| Prop | erty Frontage Width: | ft |
| | Driveway Width | |
| y Line | _ftft | ft Property Line |
| Property Line | Width at Berm ft | ty Line |

Pre-pour Apron Inspections are required. Contact the Planning and Zoning office at (330) 725-8313 twenty four (24) hours prior to pouring the apron.

Autumn Ridge, Deer Creek, Hunters Glen, Maplewood Farm and Estates, Rustic Hills, Summerset Woods Subdivision and Guilford, Paradise, Poe, and Ridgewood Roads - apron connections require an 18-24 inch cutback/stepdown connection when creating a concrete driveway and is the responsibility of the builder/homeowner to fill in said stepdown with asphalt.

Responsibility: If this permit is granted, I/we agree to comply with all the conditions, restrictions and regulations of the Township Trustees in such cases made and required. If this permit is granted, I/we hereby agree to construct that part of the driveway within the road right-of-way (apron) at an approved profile as shown on the Montville Township Driveway Detail above. I/We also agree to refrain from constructing curbs or headwalls in the shoulder area that could create hazards or hamper maintenance operations such as snowplowing.

I/We also agree that when, in the course of construction of the proposed driveway, workmen or vehicles are required to be on the pavement or shoulder, that I/we provide and maintain lights, signs, barricades, flagmen, and/or watchmen for the protection of the public and the workmen in accordance with the Ohio Manual of Uniform Traffic Control Devices for Streets and Highways, Part 7, (Construction and Maintenance Operations). Construction drives shall be properly maintained with enough stone to prevent tracking of mud and debris onto the roadways. NOTE: All sod, topsoil or unstable material must be removed from the shoulder, ditch slopes and drive bottom before constructing drive.

| Owner/Builder Signature | | | Date | |
|--|------------|--------------------|--|--|
| Twp Rd. No | Berm Width | | DWNSHIP USE ONLY: _ Length and diameter of drive pipe, if needed of inch | |
| Direction of the flow Depth of ditch Ditch structure: Straight Curve Level Hilly | | | | |
| Additional requirement | nts: | | | |
| Initial staked inspecti | on: | by | Curb-cut made: | |
| Apron paved: | Co | omments/instructio | ns: | |
| Date of final inspection | on: | by | Adopted by Trustees and Effective on Aug. 9, 2016 | |